

# BF GLITTER

## PRODUCT DESCRIPTION

The BF GLITTER SERIES is made up of 10 covering polyurethane films with glitter included into the working process. This type of processing guarantees the smooth, shiny and glittered effect at the same time.

The semi-gloss thermo-adhesive makes the cutting line highly visible and its adhesive polyester backing allows for quick weeding and easy repositioning of accidentally removed characters.

The 100-micron thickness and its elasticity make the BF GLITTER series pleasant to the touch and conformable on any fabric and suitable for multilayer applications. It is resistant to washing up to 60°C.

## APPLICATION INSTRUCTIONS

- Mirror cut BF GLITTER, with a 45° blade.
- Weed the BF GLITTER and remove the excess materials.
- Pre-heat your press to 145°C.
- Place the garment on the lower platen of your heat press.
- Place your BF GLITTER design on the garment.
- Press at 145 ° C for 10 seconds.
- Peel the carrier

## STANDARD SIZES

- H 150 cm => available lengths:  
25 mt (upon request)
- H 100 cm => available lengths:  
25 mt (upon request)
- H 75 cm => available lengths:  
25 mt (upon request)
- H 50 cm => available lengths:  
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

## APPLICATION TIPS

- Recommended fibers: organic, synthetic, mixed.
- Ideal for layering.
- Can be applied with other B-FLEX films (ex. FATTY, GLITTER, FLOCK, etc).
- Ability to cut designs as small as 0.2 cm.
- Doesn't require Teflon sheet during the pressing phase.

## TECHNICAL DATA

Film:	PU/ Polyurethane
Thickness:	100 μ (±5%)
Carrier:	PET film – self adhesive

## APPLICATION

Temperature:	145°C - 295°F
Time:	10"
Pressure:	medium – 3,5 bar – 50 PSI

## LINER REMOVAL

Hot

## WASH RESISTANCE

First wash:	wait 12 hours after application
Max. wash temp.:	60° C
Dry clean:	NO
Softener:	YES
Bleach:	NO
Dryer:	YES

## SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:  
BF GLITTER. Rev\_2019/09\_EN