

BF PROMOTIONAL

PRODUCT DESCRIPTION

The BF PROMOTIONAL series is made up of 14 semi-gloss covering polyurethane films for logos and graphics with big dimensions.

The semi-gloss thermo-adhesive adhesive makes the cutting line highly visible. The polyester carrier is not adhesive and allows the overlapping of the engraved graphics without being applied and quick weeding.

The thickness of only 90 microns and its elasticity make the BF PROMOTIONAL series suitable for multilayer applications.

APPLICATION INSTRUCTIONS

- Mirror cut BF PROMOTIONAL, with a 45° blade.
- Weed the BF PROMOTIONAL and remove the excess materials.
- Pre-heat your press to 145°C.
- Place the garment on the lower platen of your heat press.
- Place your BF PROMOTIONAL design on the garment.
- Press at 145° C for 10 seconds.
- Wait 5-7 seconds before peeling the carrier.

STANDARD SIZES

- H 150 cm => available lengths:
25 mt (upon request)
- H 100 cm => available lengths:
25 mt (upon request)
- H 75 cm => available lengths:
25 mt (upon request)
- H 50 cm => available lengths:
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

APPLICATIONS TIPS

- Recommended fibers: organic, synthetic, mixed.
- Not recommended for layering.
- Can be applied with other B-FLEX films (ex. FATTY, GLITTER, FLOCK, etc.) .
- Ability to cut designs as small as 0.5 cm.
- Doesn't require a Teflon sheet during the pressing phase.

TECHNICAL DATA

Film:	PU/ Polyurethane
Thickness:	80 μ (±5%)
Carrier:	PET film

APPLICATION

Temperature:	145°C - 295° F
Time:	10''
Pressure:	medium – 3,5 bar – 50 PSI

LINER REMOVAL

Warm; wait 5-7 seconds before remove the liner

WASH RESISTANCE

First wash:	wait 12 hours after application
Max wash Temp.:	40° C
Dry clean:	NO
Softener:	YES
Bleach:	NO
Dryer:	YES

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:
BF PROMOTIONAL. Rev_2019/09_EN