

### PRODUCT DESCRIPTION

BFPRINT TOP/G (semi-glossy) and BFPRINT TOP/M1 (matte) are two thin polyurethane white films printable with solvent, eco-solvent and latex inks and are suitable for heat transfer on cotton fabrics, polyester, nylon Lycra and acrylic garments.

Very small letters and logos can be easily cut by all current cutting plotters after the printing process thanks to the self-adhesive PET film carrier; we recommend the BF MYLAR film as a transfer tape and as a protection during the heat transfer, and then remove it while hot.

### APPLICATION INSTRUCTIONS

- Print BF PRINTTOP
- Wait at least 8 hours after printing, before proceeding cut.
- Cut BF PRINTTOP with a laser 45° blade.
- Weed the BF PRINTTOP and remove the excess materials.
- Place the BF MYLAR film on the graphic and remove the air bubbles.
- Take off the graphic from the polyester backing.
- Pre-heat your press to 145°C.
- Place the garment on the lower platen of your heat press.
- Place the BF PRINTTOP design on your garment.
- Press at 145°C for 8 seconds.
- Peel the BF MYLAR.

### STANDARD SIZES

- H 150 cm => available lengths: (upon request)
- H 100 cm => available lengths: (upon request)
- H 75 cm => available lengths: (upon request)
- H 50 cm => available lengths: 25 mt / 12,5 mt / 5 mt / 1 mt (standard)

### APPLICATION TIPS

- Recommended fibers: organic, synthetic, mixed
- Ability to cut the designs as small as 1.0 cm

### TECHNICAL DATA

Film:	PU / Polyurethane
Thickness:	60 μ (±5%)
Carrier:	PET film – self adhesive

### APPLICATION

Temperature:	145°C - 295° F
Time:	8"
Pressure:	medium – 3,5 bar – 50 PSI

### LINER REMOVAL

Hot

### WASH RESISTANCE

First wash:	wait 12 hours after application
Max wash Temp.:	40° C
Dry clean:	NO
Softener:	NO
Bleach:	NO
Dryer:	NO

### SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:  
BF PRINTTOP G/M. Rev\_2019 / 09.