

# BF PRINTFATTY

## BF PRINTFATTYUV

**B-FLEX**  
HEAT TRANSFER VINYL

### PRINT&CUT

## PRODUCT DESCRIPTION

BF PRINTFATTY is a polyurethane heat transfer film printable with solvent, eco-solvent and latex based inks, suitable for heat transfer on any fabric. Thanks to its sticky carrier small letters and drawings can be easily cut by all current cutting plotters after the printing process. BF PRINTFATTY can be pressed on t-shirts and sportswear or uniforms for work and is ideal for small logos or drawings to add extra dimension to the garments.

BF PRINTFATTYUV is the version of the BF PRINTFATTY film compatible with UV printers. This allows the inks to dry immediately, eliminating waiting times.

## APPLICATION STEPS

- Print - do not mirror
- Cut - 60° blade
- Weed excess material
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 150°C/305°F
- Place your graphic on the shirt
- Press it - 150°C/305°F for 15 seconds
- Remove BF MYLAR - hot

## SIZES

**H 50 cm** L 10 mt / 5 mt / 2,5 mt

**H 75 cm** /

**H 100 cm** /

**H 150 cm** /

Oeko-Tex  
Standard 100  
Class I



Comply with  
regulation REACH  
n°1907/2006/EU

## SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev\_2021/03

## TECHNICAL DATA



Film: PU/polyurethane



Thickness: 750μ (±5%)



Liner: adhesive PET



Finish: opaque



Inks: solvent, eco-solvent, latex

## PLOTTER SETTING



Cut settings: do not mirror



Blade: 60°



Minimum cut: 2 cm

## APPLICATION



Temperature: 150°C - 305°F



Time: 15''



Liner removal: hot



Pressure: medium-low - 2,0 bar - 30 PSI



Textile: organic, synthetic, mixed

## WASH RESISTANCE

First wash after application wait 12 hours

Max wash temperature\* 40°C - 104°F

Dry clean ✗

Dryer ✗

\*Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

HEADQUARTERS B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

NORTH AMERICA BRANCH B-FLEX AMERICA LLC info@b-flexamerica.com | www.b-flexamerica.com

ASIA-PACIFIC BRANCH B-FLEX PACIFIC PTY LTD info@b-flexpacific.com | www.b-flexpacific.com

follow us



**BF PRINTFATTY - BF PRINTFATTYUV**

**PRINT&CUT**

- *3-D effect*
- *Suggested for fabrics with smooth surfaces*
- *Also available for UV printers*