GIMME5

CAD CAM

PRODUCT DESCRIPTION

"Whether I customize cotton t-shirts, hoodies, or work pants, which heat transfer vinyl can offer ease of use while guaranteeing a long-lasting result?" We created GIMME5 to answer that question. It applies in just 4 seconds at 140°C/285°F, it offers a wide color selection, is fully opaque even on dark garments, and has an elegant matt finish. Thanks to its thickness of only 80 microns, GIMME5 is pleasant and soft on any garment and easy to use. This film is made using only the highest quality raw materials, which ensures a long-lasting application. We have tested it to last over 100 wash cycles at 90°C/194°F.

APPLICATION TECHNIQUES

- Knockout ٠
- Multi-layer, suggested up to 5 layers
- Layering with other products •

APPLICATION STEPS

- Cut 45° blade
- Weed excess material
- Turn on your heat press heat to 140°C/285°F •
- Place your graphic on the garment •
- Press it 140°C/285°F for 4 seconds •
- Remove the liner hot

SIZES

H 50 cm	L 25 mt / 12,5mt / 5 mt / 1 mt
H 75 cm	L 25 mt (upon request)
H 100 cm	L 25 mt (upon request)
H 150 cm	L 25 mt (upon request)

Oeko-Tex	OEKO-TEX®	Comply with
Standard 100	STANDARD 100	regulation REACH
Class I	Tested for harmful substances. www.eeko-tex.com/standard100	n°1907/2006/EU



TECHNICAL DATA

Film: PU/polyhurethane

- Thickness: 80µ (±5%)
- Liner: adhesive PET
- Finish: opaque

PLOTTER SETTING



- Cut settings: mirror
- - Minimum cut: 0,1 cm

Blade: 45°

APPLICATION

Temperature: 140°C - 285°F Time: 4" Liner removal: hot Pressure: medium - 3,5 bar - 50 PSI Textile: organic, synthetic, mixed

WASH RESISTANCE

wait 12 hours
90°C - 194°F
\checkmark
\checkmark

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2021/03



GIMME5			Color	Code Roll Length	BIFLE HEAT TRANSFER VINYL		
					COLOUR GUIDE		
) Applicat	tion in only 4 se	econds			~ ~~		
 Easy to Fully on 	weed aque and ideal	for laverina			GI	MME.	5
runy op		jor ayering					
FIVE 700A WHITE	FIVE 733A CARROT ORANGE	FIVE 731A ICY PINK	FIVE 770A PURPLE	FIVE 784A STEEL BLUE	FIVE 752A APPLE GREEN	FIVE 787A LIGHT TURQUOISE	FIVE 763A CAPPUCCINO
EIVE 728A EMON YELLOW	FIVE 735A CORAL RED	FIVE 736A PINK	FIVE 767A ORCHID PURPLE	FIVE 743A LILAC	FIVE 754A GRASS GREEN	FIVE 783A AQUAMARINE	FIVE 768A SAND
IVE 720A	FIVE 732A	FIVE 765A	FIVE 745A	FIVE 744A	FIVE 750A	FIVE 782A	FIVE 766A
AEDIUM YELLOW	FLAME RED	FLAMINGO PINK	PERIWINKLE	LIGHT BLUE	GREEN	TURQUOISE	BEIGE
IVE 722A	FIVE 730A	FIVE 738A	FIVE 748A	FIVE 746A	FIVE 780A	FIVE 760A	FIVE 712A
PUMPKIN YELLOW	RED	CYCLAMEN	NAVY BLUE	SKY BLUE	FOREST GREEN	BROWN	LIGHT GREY
FIVE 727A	FIVE 762A BORDEAUX	FIVE 739A VELVET RED	FIVE 747A MIDNIGHT BLUE	FIVE 741A POWDER BLUE	FIVE 781A OLIVE GREEN	FIVE 764A LEATHER	FIVE 714A GREY
FIVE 729A GALMON	FIVE 773A LAVENDER	FIVE 761A AUBERGINE	FIVE 742A ELECTRIC BLUE	FIVE 749A ICY BLUE	FIVE 788A MINT GREEN	FIVE 769A CARAMEL BEIGE	FIVE 710A BLACK
	EN/E 2225						
FIVE 734A DRANGE	FIVE 737A BLUSH PINK	FIVE 777A BLACKBERRY	FIVE 740A ROYAL BLUE	FIVE 751A LIME GREEN			

