BF PRINT02
BF PRINT02 GLOSSY

B-FLEX HEAT TRANSFER VINYL

PRINT&CUT

PRODUCT DESCRIPTION

BF PRINT02 (opaque) and BF PRINT02G (glossy) are polyurethane transparent films, printable with solvent, eco-solvent and latex inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments.

You must mirror when printing and cutting on this film.

It can be applied directly to the fabric, thus eliminating the need for any application tape.

TECHNICAL DATA

- Film: PU/Polyurethane
- Thickness: 50µ (±5%)
- Liner: adhesive PET
- Finish: BF PRINT02 opaque
  BF PRINT02G glossy
- Inks: solvent, eco-solvent, latex

PLOTTER SETTING

- Cut settings: mirror
- Blade: 45°
- Minimum cut: 2 cm

APPLICATION

- Temperature: 150°C - 305°F
- Time: 10''
- Liner removal: semi-hot
  wait 6/7 seconds
- Pressure: medium - 3,5 bar - 50 PSI
- Textile: organic, synthetic, mixed

APPLICATION STEPS

- Print - mirror
- Cut - 45° blade
- Weed excess material
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 150°C/305°F
- Place your graphic on the garment
- Press it - 150°C/305°F for 10 seconds
- Wait 6/7 seconds
- Remove BF MYLAR - semi-hot

SIZES

H 50 cm	*L*	*25 mt / 12,5 mt / 5 mt*
H 75 cm	*L*	*25 mt*
H 100 cm	*L*	*25 mt*
H 150 cm	*L*	*25 mt*

Oeko-Tex Standard 100 Class I

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 19CX00033 CENTROCOT Tested for harmful substances. www.oeko-tex.com/standard100

*Comply with regulation **REACH n°1907/2006/EU***

WASH RESISTANCE

First wash after application	*wait 12 hours*
*Max wash temperature**	*40°C / 104°F*
Dry clean	✗
Dryer	✗

**Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.*

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03

follow us

HEADQUARTERS **B-FLEX ITALIA S.r.l.** info@b-flexitalia.com | www.b-flexitalia.com
NORTH AMERICA BRANCH **B-FLEX AMERICA LLC** info@b-flexamerica.com | www.b-flexamerica.com
ASIA-PACIFIC BRANCH **B-FLEX PACIFIC PTY LTD** info@b-flexpacific.com | www.b-flexpacific.com

B-FLEX
HEAT TRANSFER VINYL

BF PRINT02-BFPRINT02 GLOSSY

PRINT&CUT

- *Trasparent finish; perfect on light colors*
- *Matte and glossy finishes available*
- *Soft touch*

B-FLEX ITALIA S.r.l. | Via 1° Maggio, 44 | 36050 Sovizzo (VI) ITALY | Ph +39 0444.028139 | info@b-flexitalia.com | www.b-flexitalia.com